

# SERIES "MCSP" SELECTION CHART

This chart shows the proper components required for ordering "MCSP" series standard Self-Priming Thermoplastic Centrifugal Pumps. To order simply: Select the series and size pump you need from the brochures and performance curves. Then select one option from each of the 4 categories shown in the column below and write its code after the series & size designation.

## CATEGORY SELECTION:

### SERIES:

**MCSP** Standard Self-Priming Thermoplastic Centrifugal Pumps.

### SIZE:

27500  
50500  
80500

### MATERIAL:

P - Polypropylene  
V - PVDF ( Kynar )  
F - PVF ( Polypropylene Head / PVDF Internals )

### PORTS:

T - FNPT Threaded  
F - ANSI 150# Flanges  
H - \* Hose Barbs

### MOTOR DRIVE:

1 - TEFC, Close-Coupled, 3 phase  
2 - UL-EXP, Close-Coupled, 3 phase  
3 - Bearing Pedestal for Base Mounting  
4 - Complete Close Coupled pump, less motor

150# ANSI Flanged Ports are standard.

For Specific Materials of Construction Refer to Production Code Sheet.



*MCSP50502 Bearing Pedestal*

## ORDERING EXAMPLE:

	MCSP	50502	P	5
SERIES:	MCSP			
SIZE:	50502			
MATERIAL:	Polypropylene			
MOTOR DRIVE:	Bearing Pedestal			