

WARRENDER, LTD.

SERIES "MT" SELECTION CHART

This chart shows the proper components required for ordering "MT" series standard Thermoplastic Regenerative Turbine Pumps.

To order simply:

Select the series and size pump you need from the brochures and performance curves.

Then select one option from each of the 6 categories shown in the column below and write its code after the series & size designation.

CATEGORY SELECTION:

SERIES:

MT Thermoplastic Regenerative Turbine Pumps.

SIZE:

2003
3002
3003
5002
5003
7002
7003
9002
16002

MATERIAL:

P- Polypropylene

V- PVDF (Kynar)

F- PVF (Polypropylene Head / PVDF Internals)

MAGNETIC COUPLING:

1- Ferrite (**DISCONTINUED**)

2- Samarium Cobalt

3- Dual CS

PORTS:

T- FNPT Threaded

F- ANSI 150# Flanges

H- * Hose Barbs

MOTOR DRIVE:

1- TEFC, Close-Coupled, 3 phase

2- * TEFC, Closed-Coupled, 1 phase

3- UL-EXP, Close-Coupled, 3 phase

4- * UL-EXP, Close-Coupled, 1 phase

5- Bearing Pedestal for Base Mounting

6- Complete Close Coupled pump, less motor

ORDERING EXAMPLE

MT 7003 P 2 F 1



* Available on Models MT2002 thru MT7002 **ONLY**

For Specific Materials of Construction Refer to Production Code Sheet.